

WD Black[™] PC Hard Drives

WD Black performance storage is designed to enhance your PC experience across heavier computing tasks whether you are a digital artist, video editor, photographer, or gamer. Available with up to 128MB of DRAM cache on higher capacity models, the WD Black drive is optimized for drive performance so you can spend more time experiencing the things you love most.



INTERFACE SATA 6 Gb/s FORM FACTOR 3.5-inch

PERFORMANCE CLASS 7200-RPM Class

CAPACITIES 500GB to 6TB

MODEL NUMBERS

WD6002FZWX WD6001FZWX WD5001FZWX WD2003FZEX WD1003FZEX WD5003AZEX

WD4004FZWX WD3003FZEX

Product Features

Inspiring performance and capacity

WD Black™ performance storage is designed to enhance your PC experience across heavier computing tasks whether you are a digital artist, video editor, photographer, or gamer. Available with an impressive 128MB of DRAM cache on higher capacity models, the WD Black PC drive is optimized for drive performance so you can spend more time experiencing the things you love most. Enhance your PC's performance even further when you combine a WD Black drive with an SSD for a dual drive configuration, allowing you to benefit from the additional caching of your operating system onto the SSD for increased performance. All together, the WD Black drive gives you the hard drive performance, capacity and an industry leading 5-year limited warranty for an inspiring three-in-one storage solution

For Creative Professionals

When it comes to storing your creativity and entire digital portfolio, look no further than WD Black performance storage for your best solution. Use the WD Black drive for storing your large multimedia files of photos, videos, games or applications and programs because with a WD Black drive, you get the best combination of speed, capacity and large cache sizes.

For Gamers

The WD Black drive is the perfect storage solution for your gaming machine by offering large capacities to store your game's downloadable content (DLC), large cache sizes, and it is the perfect compliment for maximum system performance when combined with an SSD. The WD Black drive also includes StableTrac™ Technology (2TB and larger models) for more accurate data tracking and help to reduce any impact due to vibrations from additional gaming hardware. The WD Black drive also offers a 5-year limited warranty to match or beat your other gaming hardware warranties.

Increased Reliability

The WD Black drive is equipped with StableTrac Technology (2TB and larger models) by securing the motor shaft inside to increase reliability and help reduce impact due to system-induced vibrations from other components. By stabilizing the platters inside, the WD Black drive results in more accurate tracking in a particular sector during read and write operations, optimizing performance and reliability.

Increased DRAM cache

The WD Black drive delivers high-speed transfer speeds and read rates of your files with impressive cache sizes of up to 128MB of DRAM on our high capacity models. WD's Dynamic Cache Technology improves caching algorithms in real time to allocate and optimize cache between reads and writes. This movement of cache for read data helps to reduce congestion and increase overall performance.

Applications

- · Power computing applications such as video and photo editing, and maxed out gaming computers.
- Desktop / Consumer RAID Environments WD Black PC Hard Drives are tested and recommended for use in consumer-type RAID applications (RAID o and RAID 1).*
 - Business Critical RAID Environments WD Black PC Hard Drives are not recommended for and are not warranted for use in RAID environments utilizing Enterprise HBAs and/or expanders and in multi-bay chassis as they are not designed for, nor tested in, these specific types of RAID applications. For all Business Critical RAID applications, please consider WD's Enterprise Hard Drives that are specifically designed with RAID-specific, time-limited error recovery (TLER), are tested extensively in 24×7 RAID applications, and include features for Enterprise-type applications.



Specifications	6ТВ	6ТВ	5TB	4ТВ	зТВ
Model number ¹	WD6002FZWX	WD6001FZWX	WD5001FZWX	WD4004FZWX	WD3003FZEX
Interface²	SATA 6 Gb/s				
Formatted capacity ²	6TB	6TB	5TB	4TB	зтв
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Advanced Format (AF)	Yes	Yes	Yes	Yes	Yes
RoHS compliant³	Yes	Yes	Yes	Yes	Yes
Performance					
Data transfer rate (max)² Buffer to host Host to/from drive (sustained)	6 Gb/s 227 MB/s	6 Gb/s 218 MB/s	6 Gb/s 194 MB/s	6 Gb/s 202 MB/s	6 Gb/s 168 MB/s
Cache (MB)	128	128	128	128	64
Performance Class (RPM)	7200-RPM Class				
Reliability/Data Integrity					
Load/unload cycles⁴	300,000	300,000	300,000	300,000	300,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁴				
Limited warranty (years)⁵	5	5	5	5	5
Power Management					
Average power requirements (W) Read/Write Idle Standby/Sleep	9.1 7.1 1.0	10.6 7.6 1.6	10.6 7.6 1.6	9.1 5.8 1.0	9.5 8.1 1.3
Environmental Specifications					
Temperature (°C) Operating Non-operating	5 to 55 -40 to 70				
Shock (Gs) ⁶ Operating (2 ms, write) Operating (2 ms, read) Non-operating (2 ms)	30 65 300	30 65 300	30 65 300	30 65 300	30 65 300
Acoustics (dBA) ⁷ Idle Seek (average)	29 36	31 34	31 34	29 36	29 34
Physical Dimensions					
Height (in./mm, max)	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg,)	1.58/0.72 ± 3%	1.66/0.75 ± 3%	1.66/0.75 ± 3%	1.58/0.72 ± 10%	1.40/0.64 ± 10%

 $^{^{1}\,}$ Not all products may be available in all regions of the world.

As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second, (MB/s) = one million bytes per second, and gigabit per second (GB/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

³ WD hard drive products manufactured and sold worldwide after June 8, 2011, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

⁴ Controlled unload at ambient condition.

 $^{^{5}\,}$ The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

 $^{^{\}rm 6}$ No non-recoverable errors during operating tests or after non-operating tests.

⁷ Sound power level ·



Specifications	зТВ	2TB	1TB	500GB
Model number ¹	WD3003FZEX	WD2003FZEX	WD1003FZEX	WD5003AZEX
Interface ²	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s
Formatted capacity ²	зТВ	2TB	1TB	500GB
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Advanced Format (AF)	Yes	Yes	Yes	Yes
RoHS compliant ³	Yes	Yes	Yes	Yes
Performance				
Data transfer rate (max)² Buffer to host Host to/from drive (sustained)	6 Gb/s 168 MB/s	6 Gb/s 164 MB/s	6 Gb/s 150 MB/s	6 Gb/s 150 MB/s
Cache (MB)	64	64	64	64
Performance Class (RPM)	7200-RPM Class	7200-RPM Class	7200-RPM Class	7200-RPM Class
Reliability/Data Integrity				
Load/unload cycles ⁴	300,000	300,000	300,000	300,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁴			
Limited warranty (years) ⁵	5	5	5	5
Power Management				
Average power requirements (W) Read/Write Idle Standby/Sleep	9.5 8.1 1.3	9.5 8.1 1.3	6.8 6.1 0.8	6.8 6.1 0.8
Environmental Specifications				
Temperature (°C) Operating Non-operating	5 to 55 -40 to 70	5 to 55 -40 to 70	0 to 60 -40 to 70	0 to 60 -40 to 70
Shock (Gs) ⁶ Operating (2 ms, write) Operating (2 ms, read) Non-operating (2 ms)	30 65 300	30 65 300	30 65 350	30 65 350
Acoustics (dBA) ⁷ Idle Seek (average)	29 34	29 34	29 30	29 30
Physical Dimensions				
Height (in./mm, max)	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.40/0.64 ± 10%	1.32/0.60	0.99/0.45	0.95/0.43

¹ Not all products may be available in all regions of the world.

Western Digital 3355 Michelson Drive, Suite 100 Irvine, California 92612 U.S.A.

For service and literature:

www.wdc.com

800.ASK.4WDC (800.275.4932) 800.832.4778 +86.21.2603.7560 00800.27549338

North America English Spanish Asia Pacific Europe

(toll free where available) +31.880062100 Europe/Middle East/Africa





















Western Digital, WD, the WD Logo, FIT Lab, StableTrac, WD Black and WD Blue are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the U.S. and/or other countries. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice. Pictures shown may vary from actual products.

© 2016 Western Digital Corporation or its affiliates. All rights reserved.

2879-771434-A11 December 2016



As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

³ WD hard drive products manufactured and sold worldwide after June 8, 2011, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

⁴ Controlled unload at ambient condition.

 $^{^{5}}$ The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

 $^{^{\}rm 6}$ No non-recoverable errors during operating tests or after non-operating tests.

⁷ Sound power level